- 1. Chamber Volume: 176 Liters or more
- 2. Footprint should not exceed : 0.47m²
- 3. The ovens should have mechanical convection
- 4. Temperature Range 50° C to 250° C
- 5. Spacial Temperature Deviation at 150° C : $\pm 2.8^{\circ}$ C
- 6. Temperature Deviation over Time at 150° C : $\pm 0.3^{\circ}$ C
- 7. The Inner chamber should be made of AISI 430 / 1.4016 Stainless Steel
- 8. The Ovens should have an automatic over temperature alarm
- 9. The ovens interior should have rounded corner for ease of clean and better contamination control
- 10. The system should have shelving system that can be fitted inside the chamber with just one click
- 11. The ovens interface should be microprocessor controlled and should be a vacuum fluorescent display with touch button control.
- 12. The oven should be provided with 2 shelves as standard and should be capable of accommodating a maximum of 19 shelves
- 13. Each of the shelves should be capable of accommodating a load of 25 Kg
- 14. The oven should have a manual damper for venting out the chamber air
- 15. The ovens should be covered with 2 years of warranty
- 16. The oven should have RS 232 interface providing data logging capability
- 17. The ovens should be stackable with optionally available stacking kit
- 18. The ovens should have the basic on/off timer to automate on and off cycle after a preset time.
- 19. The door should be able to open at 180° angle for complete access to chamber interior.
- 20. The ovens should have optional accessories like additional shelf, stacking kit and support stand with castors
- 21. The ovens should be able to operate at 230 V $\,$ / 50 Hz